

Divide the consumption in 10, multiply the lifespan of the product.

	Bipin	Dichroic	Light bulbs	High power light bulbs	PAR	UL
Protection grade	IP20	IP20	IP20	IP20	IP20	IP64
Material	Plastic	Plastic	Plastic	Plastic	Plastic	Plastic
Diffuser	Transparent	Lens	Translucent	Translucent	Lens	Transparent
Power supply	Internal / External	Internal / External	Internal / External	Internal / External	Internal / External	Internal / External




- 5700K (5310-6020) **F** Freeze/Frío
- 5000K (4800-5300) **C** Cold/Natural
- 4000K (3800-4300) **N** Neutral/Neutro
- 2700K (2500-2900) **W** Warm/Cálido



	Type	Total consumption (W) ⁽²⁾	Code	Dimensions AxB (mm)	Weight (g)	Input voltage (V/Hz)	THDi (%)	Luminous flux (lm) ⁽²⁾	Efficiency (lm/W) ⁽²⁾	Angle to 50% (°)	Power Factor ⁽¹⁾
Bipin	G9	2,3	G923 W	Ø20x53	10	220-240	<65	209	91	280°	0,4
Dichroic	MR16	4,5	MR164 W	Ø50x50	60	12V DC	-	395	88	40°	-
	MR16	7,5	MR167 W	Ø50x64	69	12V DC	-	550	73	36°	-
	GU10	4,5	GU104 W	Ø51x57	60	220-240	<190	405	90	40°	0,5
	GU10	7	GU107 W B	Ø51x57	60	220-240	<90	665	95	40°	0,8
Bulbs	E14	5,3	E145 W C	Ø35x104	40	200-240	<175	450	85	150°	0,9
	E27	5	E275 W	Ø60x114	110	200-240	<175	500	100	200°	0,5
	E27	5	E275 C B	Ø60x114	110	200-240	<175	625	125	200°	0,5
	E27	8	E278 W	Ø60x114	110	200-240	<160	810	101	200°	0,5
PAR	PAR20	7,5	L20 (N/W) 8D	Ø63x86	200	220-240	<32	650	87	25°	0,9
	PAR30	11	L30 (N/W) 11	Ø95x86	190	220-240	<22	965	88	25°	0,9
	PAR38	17	L38 (N/W) 17	Ø120x129	360	220-240	<22	1405	83	25°	0,9
High power bulbs	E27	18,5	E2702 (N/W)	Ø80x150	300	220-240	<25	2035	110	150°	0,9
	E27	27	E2703 (N/W)	Ø100x185	360	220-240	<25	2430	90	150°	0,9
	E27	36	E2704 (N/W)	Ø118x213	490	220-240	<25	3240	90	150°	0,9
	E40	65	E4007 C	Ø118x268	500	100-277	<25	8125	125	160°	0,9

⁽¹⁾110V bulbs. Check availability

Light bulbs with UL certification, Approved for the U.S.A.



	Type	Total consumption (W) ⁽²⁾	Code	Dimensions AxB (mm)	Weight (g)	Input voltage (V/Hz)	THDi (%)	Luminous flux (lm) ⁽²⁾	Efficiency (lm/W) ⁽²⁾	Angle to 50% (°)	Power Factor ⁽¹⁾
UL Bulbs	E39	30	E3930 C UL	Ø93x230	440	100-277	<15	3900	130	360°	0,9
	E39	60	E3960 C UL	Ø93x285	570	100-277	<15	7800	130	360°	0,9
	E39	120	E39A2 C UL	Ø125x310	1240	100-277	<15	15600	130	360°	0,9
	E39	150	E39A5 C UL	Ø125x335	1340	100-277	<25	19500	130	360°	0,9