



Ideal for retail outlets and display requirements.
Maximize the results of your products with the different colours, potency and angles.
The best lighting quality with products up to 95 CRI

	COB	COB pink	RGBW
Protection grade	IP20	IP20	IP20
Material	Aluminum	Aluminum	Aluminum
Diffuser	-	-	-
Power supply	Internal	Internal	Internal
Regulations	No	No	No
Power factor ⁽¹⁾	0,95	0,95	0,95
Angle to 10% / 50%	>37°/24°	>73°/30°	12 a 24°

5000K (4800-5300) Cold/Natural
4000K (3800-4300) Neutral/Neutro
3000K (2800-3300) Warm/Cálido
Rosado (2200-3300) Pink/Rosa



	Type	Total consumption (W) ⁽²⁾	Code ⁽⁴⁾	Dimensions AxB (mm)	Weight (g)	Input voltage (V AC)	THDi (%)	DC Voltage (V)	DC current (mA)	Luminous flux (lm) ⁽³⁾	Efficiency (lm/W) ⁽³⁾	CRI \geq
COB	White	20	TL20(W)D	Ø95x231x135	905	220-240	<23	32-37	500	2600	130	80
	White	30	TL30(W)E	Ø95x211x125	950	100-277	<15	32-37	790	3600	120	80
	White	40	TL40(W)E	Ø95x221x140	1000	100-277	<15	32-37	1050	4800	120	80
COB pink	White	40	TLC4(P)30W	Ø100x164x210	1160	100-277	<15	33-37	1000	1900	48	80
RGBW	Foco	RGBW	TL85R24	Ø120x188x250	2300	220-240	<12	-	-	4500	53	90
	Acces.	Router WIFI DMX	TLROUT	134x85x35	350	220-240	It allows to control up to 30 RGBW spotlights					



Description	Triphase rail	
	White	Black
Threephase aluminum rail 1 m	TLCAR1WC	TLCAR1BC
Threephase aluminum rail 2 m	TLCAR2WC	TLCAR2BC
Rail supply+End cap	TLCAIWC	TLCAISC
Internal Union	TLCUWC	TLCUC
Flexible elbow for the rail connection 90°	TLC90WC	TLC90BC
Suspension cable for the installation 1200mm	TLCAC12W	TLCAC12B

(1) Data ± 5%
(2) Data ± 10%
(3) The data shown correspond to the color 5000k-c Cold. To obtain 4000k subtract 4% to get color data 10%
(4) Check other colors